

**20034607W****3.5" MINI TOUCH SIMPLEHOME SUPERVISOR - WHITE**

Mini Touch 3,5" with a supervisory function. To be connected to BUS SimpleHome for the management of the automation system to control lights, loads, shutters, climate, scenary and the irrigation system and to SimpleSafe system for visualisation and operation of the burglar alarm syste . Integrated temperature sensor, 1 changeover relay output. RFID integrated reader to activate scenarios from transponder art.SK9050. RGB adjustable and Magic Light Indicator function with change of colour depending on the status of the areas climate and according to the status of the burglar system. Suitable for installation on standard box 3 modules or civil series. size 125x85mm. 10mm projection wall. Consumption 2W.



20034607W

3.5" MINI TOUCH SIMPLEHOME SUPERVISOR - WHITE

GENERAL DATA

Height (mm)	125
Width (mm)	85
Depth (mm)	10
Product color	White
Type of finishing materials	ABS, Glass

COMPATIBILITY

Home Automation system	Yes
------------------------	-----

DISPLAY

Touch screen	Yes
OSD menu	Yes

ELECTRICAL SPECIFICATIONS

Type of power supply	Powered by SimpleHomeBus home automation bus
Supply voltage	12/24Vdc
Maximum absorption (W)	2

HARDWARE SPECIFICATIONS

Temperature sensor	Yes
--------------------	-----

ENVIRONMENTAL AND COMPLIANCE FEATURES

CE certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)
-------------------	--

DOMOTIC FUNCTIONS

Lights management	Yes
Rolling shutter/Venetian blind control	Yes
Temperature and humidity control	Yes
Scenario management	Yes



20034607W

3.5" MINI TOUCH SIMPLEHOME SUPERVISOR - WHITE

SECURITY FUNCTIONS

Activation/deactivation management	Yes
System status view	Yes

MAIN FEATURES

No. scenarios (n°)	50
No. of Simplehome buses (n°)	1
Network connection	Yes
B/W or colour display	Colour
Flush-mounted box type	3 modules
Multi-speed control (fan coil) with temperature sensor	Yes
No. conditioned scenarios	Yes
SimpleHome home automation bus connection	Yes
Touch screen display	Yes
SimpleSafe anti-intrusion bus connection	Yes
Weekly programming	Yes
Display size (")	3.5
RS485 ports (n°)	1
Proximity reader RFID	Yes
Integrated temperature sensor	Yes
Bridging function from automation to anti-intrusion	Yes
Temperature setting range (°C)	5 ÷ 30
Flush-mounted	Italian standard 3-module box
Temperature reading resolution (°C)	0.1
On-board output for boiler control	Yes
On-board outputs for multi-speed control (fan coil)	Yes



20034607W

3.5" MINI TOUCH SIMPLEHOME SUPERVISOR - WHITE

MAIN FEATURES

Temperature and humidity control for other climate zones	Yes
Automation management	Yes
Loads management	Yes
Climate management	Yes
Consumption management	Yes
Integrated sensor heating/cooling control	Yes
Scheduling management	Yes
Timing management	Yes
Maximum number of scenarios managed (n°)	70
Daily/weekly programming	Yes
Display colour control	Yes
Display contrast control	Yes
Integrated sensor local temperature regulation	Yes
Display brightness control	Yes
SD card included for consumption and configuration	Yes
Integrated sensor status display	Yes
Intrusion detection system	Yes