

**G115K****VIDEO KIT WITH DOOR ENTRY MONITOR 7 PLUS**

A single-family kit consisting of a wall-mounted entrance panel already fitted with a rain shield and a 7" hands-free door entry monitor 7 Plus series with soft-touch buttons, 2-wire system.

The door entry monitor allows the recording of 100 images, this number is expandable with the addition of a micro-SD card to be purchased separately.

It is possible to control the 2 outputs on the entrance panel via 2 different buttons on the door entry monitor.

The system is expandable with a second door entry monitor art. G116V, and its power supply art. G116A, to be purchased separately. The addition of the second door entry monitor makes the intercom function available.

The kit is supplied ready for use and complete with all the accessories required for installation. Suitable for installation in residences, businesses or offices.

**G116V**

**DOOR ENTRY MONITOR FOR KIT ART. G115K**

**GENERAL DATA**

Height (mm)	127
Width (mm)	180
Depth (mm)	15
Product color	White
Wall-mounted	Yes
Type of finishing materials	Plastic

**DISPLAY**

Display size	7"
Aspect Ratio	16:9
Resolution (pixels)	800 x 480
OSD menu	Yes
Type of display	LCD
Date/time retention time	10 hours

**AUDIO FEATURES**

Technologies implemented	Half-duplex
--------------------------	-------------

**ELECTRICAL CHARACTERISTICS**

Type of power supply	External power supply
Supply voltage	15 VDC
Absorption in stand-by (W)	0.23
Maximum absorption (W)	5.7
Absorption during call (W)	5.5
Absorption during communication (W)	5.7

**G116V**

**DOOR ENTRY MONITOR FOR KIT ART. G115K**

**HARDWARE FEATURES**

Type of buttons	Soft touch
Memory card supported	Micro-SD, 32GB max (NOT supplied)
Total buttons	8

**SETTINGS**

Ringtone volume	Yes
Screen brightness control	Yes
Screen contrast	Yes
Screen colour	Yes

**ENVIRONMENTAL AND COMPLIANCE FEATURES**

Operating temperature (°C)	-10÷50
Operating humidity (RH max) (%)	85 max
Environmental class	I
CE certifications	EMC 2014/30/UE (EN 61000-6-1:2007, EN 61000-6-3:2007+A1:2011) RoHS II - 2011/65/UE (EN IEC 63000:2018)

**GENERAL FEATURES**

Door opener	Yes
Self Activation	Yes
Intercom calls	Yes

Silent mode (Privacy)	Yes
Video memory	Yes
Customisable ringtone	Yes
Date/time display	Yes

## ENTRANCE PANEL FOR KIT ART. G115K

### GENERAL DATA

Type	Monoblock
Height (mm)	156
Width (mm)	80
Depth (mm)	40
Product color	Silver
Wall-mounted	Yes
Type of finishing materials	Aluminium

### AUDIO FEATURES

Technologies implemented	Half-duplex
--------------------------	-------------

### CAMERA FEATURES

Camera	Colours
Sensor type	1/3" CMOS
Angle of view (H x V - °)	95 x 52
Sensitivity (lux)	0
Video resolution (H x V - pixel)	800 x 480

### ELECTRICAL CHARACTERISTICS

Supply voltage	15 VDC
Absorption in stand-by (W)	0.05
Maximum absorption (W)	1.25

## ENTRANCE PANEL FOR KIT ART. G115K

### HARDWARE FEATURES

Type of buttons	Mechanical
Number of push-buttons	1
Backlight colour	White
Number of outputs	2
Type of outputs	Electric lock: 8~12VDC/1A Relay: 12/24 VAC/VDC / 1A

### ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection rating	IP44
Operating temperature (°C)	-10÷50
Operating humidity (RH max) (%)	85 max
Environmental class	I
CE certifications	EMC 2014/30/UE (EN 61000-6-1:2007, EN 61000-6-3:2007+A1:2011) RoHS II - 2011/65/UE (EN IEC 63000:2018)

### MAIN FUNCTIONS

Door opener	Yes
Number of auxiliary relays	1

**G116A**

**POWER SUPPLY FOR ART. G116V**

**GENERAL DATA**

Height (mm)	56
Width (mm)	76
Depth (mm)	93
Type of finishing materials	Plastic
Product color	White
Applicable to DIN rail	Yes

**ELECTRICAL CHARACTERISTICS**

Supply voltage	100÷240VAC / 50÷60Hz
Output supply voltage	12÷17VDC
Maximum current delivered	2A
Maximum power delivered (W)	30

**ENVIRONMENTAL AND COMPLIANCE FEATURES**

Operating temperature (°C)	-10÷50
Operating humidity (RH max) (%)	85 max
Environmental class	I
CE certifications	EMC 2014/30/UE (EN 61000-6-1:2007, EN 61000-6-3:2007+A1:2011) RoHS II - 2011/65/UE (EN IEC 63000:2018)